

# crane support plates

status: 16.07.2019

ground pressure:  
50N/cm<sup>2</sup>, 50 to/m<sup>2</sup>, 5 kg/cm<sup>2</sup>

(\*support area)

	plate	load capacity	stamp size	dimension	expanse	ground pressure	weight
	no.	to	mm	L x B x H mm	m <sup>2</sup>	approx. to / m <sup>2</sup>	approx. to
T	K-KP-093	30	400	1010 x 1000 x 190	1,10	30	0,30
B	K-KP-107	40	350	1200 x 1200 x 200	1,40	27	0,56
T	K-KP-019	50	800	1800 x 1300 x 150	2,34	21	0,60
T	K-KP-025	50	600	1700 x 1210 x 190	2,06	24	0,55
T	K-KP-025.1	50	600	1600 x 1210 x 190	1,92	26	0,50
B	K-KP-069.1	50	400 (2500 x 700*)	3000 x 1150 x 200	3,45	14	1,40
T	K-KP-106	50	500	1010 x 1000 x 190	1,00	50	0,27
T	K-KP-002	70	600	1690 x 1460 x 150	2,46	28	0,55
T	K-KP-002.1	70	600	2000 x 1300 x 150	2,60	26	0,65
T	K-KP-002.2	70	600	2000 x 1460 x 150	2,92	23	0,70
T	K-KP-002.3	70	600	2500 x 1250 x 150	3,13	22	0,80
B	K-KP-039	70	600	2000 x 1000 x 200	2,00	35	0,60
B	K-KP-073	80	550	2000 x 1200 x 200	2,40	33	0,85
B	K-KP-078	80	550	1500 x 1500 x 200	2,25	35	0,80
B	K-KP-086.1	80	600	1500 x 1200 x 220	1,80	44	0,65
B	K-KP-086.2	80	600	1700 x 1200 x 220	2,04	39	0,75
B	K-KP-086.3	80	600	1900 x 1200 x 220	2,28	35	0,85
B	K-KP-109	80	500	2500 x 1500 x 200	3,75	21	1,05
B	K-KP-079	85	700	1500 x 1200 x 200	1,80	47	0,60
T	K-KP-021	90	800	1820 x 1800 x 170	1,80	50	0,80
T	K-KP-021.1	90	800	2000 x 1200 x 170	2,40	37	0,65
T	K-KP-021.2	90	800	1500 x 1200 x 170	1,80	50	0,42
B	K-KP-032	90	600	2000 x 1500 x 220	3,00	30	1,10
B	K-KP-032.1	90	600	2400 x 1540 x 220	3,70	24	1,30
T	K-KP-034.3	90	600	2200 x 2000 x 180	4,40	20	1,35
B	K-KP-038	90	500	2500 x 1100 x 200	2,75	32	0,90

ground pressure:  
50N/cm<sup>2</sup>, 50 to/m<sup>2</sup>, 5 kg/cm<sup>2</sup>

(\*support area)

	plate	load capacity	stamp size	dimension	expanse	ground pressure	weight
	no.	to	mm	L x B x H mm	m <sup>2</sup>	approx. to / m <sup>2</sup>	approx. to
B	K-KP-034	100	600	1600 x 1600 x 180	2,56	39	1,10
B	K-KP-034.1	100	600	1800 x 1800 x 180	3,24	30	1,20
B	K-KP-034.2	100	600	2000 x 2000 x 180	4,00	25	1,30
B	K-KP-082	100	600	2000 x 1500 x 200	3,00	33	1,10
T	K-KP-092	100	600 (1000 x 800*)	2300 x 1630 x 170	3,75	26	0,80
B	K-KP-096.1	100	500	2500 x 1500 x 220	3,75	27	1,30
BF	K-KP-097	100	500	1500 x 1200 x 140	1,80	55	0,48
T	K-KP-102	100	600	2500 x 1630 x 170	4,07	24	1,00
B	K-KP-108	100	700	3000 x 1500 x 220	4,50	23	1,60
T	K-KP-013.1	120	800	2480 x 1630 x 170	4,04	29	0,95
T	K-KP-013.2	120	800	2400 x 2360 x 170	5,66	21	1,35
T	K-KP-013.3	120	800	2480 x 2200 x 170	5,46	21	1,30
T	K-KP-013.4	120	800	2480 x 2000 x 170	4,96	24	1,20
T	K-KP-018	120	800	2500 x 1100 x 170	2,75	43	0,70
B	K-KP-049	120	550	2500 x 1800 x 220	4,50	26	1,50
B	K-KP-049.1	120	550	2400 x 2360 x 220	5,66	21	1,80
B	K-KP-095	120	500	2500 x 1600 x 220	4,00	30	1,50
B	K-KP-096	120	550	2500 x 1500 x 220	3,75	32	1,30
B	K-KP-022	130	700	2500 x 2000 x 200	5,00	26	1,20
B	K-KP-051	130	550	2000 x 1500 x 220	3,00	43	1,20
B	K-KP-051.1	130	500 (1200 x 800*)	2300 x 1600 x 220	3,68	35	1,50
B	K-KP-055	130	550	2500 x 2420 x 240	6,05	21	1,95
B	K-KP-058.4	130	600	2500 x 2000 x 220	5,00	26	1,60
B	K-KP-091	130	600 (1300 x 1000*)	2300 x 1608 x 220	3,68	35	1,40
T	K-KP-009	140	800	2500 x 2420 x 190	6,00	23	1,45
T	K-KP-016	140	800	2200 x 1620 x 190	3,56	39	0,95
B	K-KP-029	140	600	1750 x 1750 x 200	3,06	45	1,30
B	K-KP-029.1	140	600	2000 x 2000 x 200	4,00	35	1,40

ground pressure:  
50N/cm<sup>2</sup>, 50 to/m<sup>2</sup>, 5 kg/cm<sup>2</sup>

(\*support area)

	plate	load capacity	stamp size	dimension	expanse	ground pressure	weight
	no.	to	mm	L x B x H mm	m <sup>2</sup>	approx. to / m <sup>2</sup>	approx. to
B	K-KP-058	140	500	2000 x 1820 x 220	3,64	38	1,25
B	K-KP-058.1	140	500	2000 x 2000 x 220	4,00	35	1,35
B	K-KP-067.2	140	500	2500 x 2400 x 300	6,00	23	2,40
B	K-KP-101	140	700	3000 x 2000 x 200	6,00	23	1,80
B	K-KP-008	150	800	2380 x 2350 x 240	5,59	26	1,75
B	K-KP-043	150	600	2300 x 2300 x 240	5,29	28	1,70
B	K-KP-043.1	150	600	2200 x 2200 x 240	4,84	30	1,65
B	K-KP-044	150	700	3250 x 2300 x 240	7,47	20	2,20
B	K-KP-048	150	600	3000 x 2300 x 240	6,90	21	2,10
B	K-KP-053	150	600	3000 x 2000 x 240	6,00	25	1,95
B	K-KP-053.1	150	600	4000 x 2000 x 240	8,00	18	2,30
B	K-KP-059.1	150	500	2500 x 2500 x 300	6,25	24	2,50
B	K-KP-062	150	600	3000 x 2400 x 240	7,20	20	2,35
B	K-KP-064	150	600	3000 x 2000 x 240	6,00	25	2,35
B	K-KP-083.1	150	700	2400 x 2400 x 200	5,76	26	1,80
B	K-KP-104	150	500	2000 x 1004 x 200	2,00	45	0,75
B	K-KP-105	150	500	2500 x 1800 x 200	4,50	33	1,60
T	K-KP-017	160	800	2000 x 1820 x 190	3,64	43	0,90
B	K-KP-024	160	600	2400 x 2200 x 220	5,28	30	1,60
B	K-KP-033	160	600	2200 x 1700 x 180	3,74	42	1,20
B	K-KP-057	160	600	3500 x 2400 x 240	8,40	19	2,40
B	K-KP-058.2	160	600	2000 x 1820 x 220	3,64	43	1,25
B	K-KP-058.3	160	600	2000 x 2000 x 220	4,00	40	1,35
B	K-KP-060.1	160	600	3500 x 2400 x 240	8,40	19	2,90
B	K-KP-047	170	600	2500 x 2000 x 200	5,00	34	1,40
B	K-KP-047.1	170	600	2400 x 2000 x 200	4,80	35	1,35
T	K-KP-015	180	800	4000 x 2420 x 230	9,68	18	2,80
B	K-KP-050.1	180	600	2500 x 2400 x 240	6,00	30	2,10

ground pressure:  
50N/cm<sup>2</sup>, 50 to/m<sup>2</sup>, 5 kg/cm<sup>2</sup>

(\*support area)

	plate	load capacity	stamp size	dimension	expanse	ground pressure	weight
	no.	to	mm	L x B x H mm	m <sup>2</sup>	approx. to / m <sup>2</sup>	approx. to
B	K-KP-052	180	800 (1250 x 700*)	3000 x 2300 x 240	6,90	26	2,25
B	K-KP-054	180	600	2800 x 2400 x 240	6,72	26	2,00
B	K-KP-056	180	700	2500 x 2250 x 200	5,63	31	1,70
B	K-KP-083	180	800	2400 x 2400 x 200	5,76	31	1,80
B	K-KP-085	180	600	2200 x 1800 x 220	3,96	45	1,20
BF	K-KP-098	180	500	2000 x 1800 x 180	3,60	44	0,80
T	K-KP-100	185	800	3000 x 2200 x 170	6,60	28	2,10
T	K-KP-007	190	800	3000 x 1940 x 230	5,82	32	1,70
B	K-KP-023.2	190	600	2400 x 2400 x 240	5,76	32	2,00
B	K-KP-023.3	190	600	2300 x 2300 x 240	5,29	35	1,90
B	K-KP-024.1	190	600	2200 x 2200 x 220	4,84	39	1,55
B	K-KP-010.1	200	700	3800 x 2400 x 240	9,12	21	2,80
B	K-KP-010.2	200	700	2400 x 2400 x 240	5,76	34	1,80
B	K-KP-014	200	800	2800 x 1600 x 240	4,48	44	1,70
B	K-KP-014.1	200	800	3000 x 2000 x 240	6,00	33	1,90
B	K-KP-014.2	200	800	3000 x 2300 x 240	6,90	28	2,20
B	K-KP-031	200	800	2500 x 2400 x 240	6,00	33	1,90
B	K-KP-050	200	550	3000 x 2300 x 240	6,90	28	2,30
B	K-KP-065	200	2 x 1000 x 1000	6000 x 2500 x 300	15,00	13	4,80
B	K-KP-067.1	200	600	2500 x 2400 x 300	6,00	33	2,40
B	K-KP-071	200	800	2000 x 2000 x 200	4,00	50	1,40
B	K-KP-071.1	200	800	2200 x 2200 x 200	4,84	41	1,80
B	K-KP-071.2	200	700	2000 x 2000 x 200	4,00	50	1,33
B	K-KP-077	200	600	4200 x 2400 x 200	10,08	19	3,00
B	K-KP-077.2	200	600	2400 x 2400 x 200	5,76	35	1,80
B	K-KP-080.1	200	600	2400 x 2400 x 240	5,76	34	1,95
B	K-KP-090	200	800	5000 x 2000 x 240	10,00	20	3,20
B	K-KP-090.1	200	600 (2000 x 1000*)	5000 x 2000 x 240	10,00	20	3,30

ground pressure:  
50N/cm<sup>2</sup>, 50 to/m<sup>2</sup>, 5 kg/cm<sup>2</sup>

(\*support area)

	plate	load capacity	stamp size	dimension	expanse	ground pressure	weight
	no.	to	mm	L x B x H mm	m <sup>2</sup>	approx. to / m <sup>2</sup>	approx. to
B	K-KP-103	200	700	6000 x 2000 x 304	12,00	17	4,75
B	K-KP-044	220	700	3250 x 2300 x 240	7,48	29	2,20
B	K-KP-063	220	600	4000 x 2000 x 240	8,00	27	2,95
B	K-KP-081	220	550	2500 x 2400 x 300	6,00	36	2,60
B	K-KP-023	240	800	2400 x 2400 x 240	5,76	41	2,00
B	K-KP-023.1	240	800	2300 x 2300 x 240	5,29	45	1,90
B	K-KP-060	240	600	4000 x 2400 x 240	9,60	25	3,20
B	K-KP-094	240	700	5000 x 2500 x 300	12,50	20	4,10
B	K-KP-010	250	800	3800 x 2400 x 240	9,12	27	2,80
B	K-KP-010.3	250	800	2400 x 2400 x 240	5,76	43	1,80
B	K-KP-066.1	250	700 exzentrisch	4000 x 2400 x 240	9,60	26	3,00
B	K-KP-080	250	800	2400 x 2400 x 240	5,76	43	1,95
B	K-KP-026	260	800	2400 x 2200 x 240	5,28	49	1,80
B	K-KP-030	260	600	3500 x 2400 x 200	8,40	30	2,70
B	K-KP-030.1	260	600	3300 x 2400 x 200	7,92	32	2,60
B	K-KP-030.2	260	600	2400 x 2400 x 200	5,76	45	2,00
B	K-KP-020.1	280	700	3780 x 2410 x 240	9,11	30	2,85
B	K-KP-067	280	800	2500 x 2400 x 300	6,00	46	2,40
B	K-KP-072	280	600	3000 x 2000 x 240	6,00	46	2,00
B	K-KP-036	300	700	3500 x 2340 x 240	8,19	36	2,60
B	K-KP-036.1	300	700	4000 x 2400 x 240	9,60	31	3,20
B	K-KP-045	300	700	2300 x 2300 x 204	5,29	56	2,00
B	K-KP-059	300	700	2500 x 2500 x 300	6,25	48	2,50
B	K-KP-066	300	800	4000 x 2400 x 240	9,60	31	3,00
B	K-KP-074.1	300	1000	6000 x 2500 x 304	15,00	20	6,00
B	K-KP-074.2	300	700	6000 x 2500 x 304	15,00	20	6,10
B	K-KP-075.1	300	1000	4500 x 2500 x 304	11,25	26	4,60
B	K-KP-040	320	800	3000 x 2000 x 240	6,00	53	2,00

ground pressure:  
50N/cm<sup>2</sup>, 50 to/m<sup>2</sup>, 5 kg/cm<sup>2</sup>

(\*support area)

	plate	load capacity	stamp size	dimension	expanse	ground pressure	weight
	no.	to	mm	L x B x H mm	m <sup>2</sup>	approx. to / m <sup>2</sup>	approx. to
B	K-KP-042	320	600	3000 x 2500 x 240	7,50	42	2,40
B	K-KP-046	320	700	3250 x 2300 x 204	7,48	42	2,70
B	K-KP-084	320	700	3500 x 2400 x 240	8,40	38	3,20
B	K-KP-084.1	320	700	3800 x 2400 x 240	9,12	35	3,60
B	K-KP-070	350	700	5940 x 2400 x 304	14,26	24	5,50
B	K-KP-099	380	700	3500 x 2400 x 280	8,40	45	3,20
B	K-KP-020	400	800	3780 x 2410 x 240	9,11	43	2,85